

Digimatic Indicator | GTDL-D41 | GTDL-D45

This product is a compact 4-channel data logger measuring digital displacement sensors, displaying graphs in real-time, and saving data using PC connection. And it is convenient to measure in long-distance and to expand channels using wireless communications.



Specification

| Range | Resolution | Accuracy | Model |
|--------|------------|----------|----------|
| 12.7mm | 0.01 | 0.02 | 543-681B |
| 12.7mm | 0.001 | 0.003 | 543-690B |
| 25.4mm | 0.01 | 0.02 | 543-474B |
| 25.4mm | 0.001 | 0.003 | 543-470B |
| 50.8mm | 0.01 | 0.02 | 543-494B |
| 50.8mm | 0.001 | 0.003 | 543-490B |



Feature

- Applying to other displacement measurement such as consolidation test, single-axis or direct shear
- Matched sensor and PC data due to digital measurement
- Improved convenience using wireless data transfer
- Able to expand channels (4ch, 8ch, 12ch, 16ch, 20ch)
- Included multiscan/multi-load program
- Wireless model (GTDL-D41)
- USB model (GTDL-D45)

Specification

| Model | GTDL-D41 | GTDL-D45 |
|-------------------|--------------------------------|------------|
| Number of Channel | 4 Channels | 4 Channels |
| Input Sensor | Digimatic Indicator (mitutoyo) | |
| Interface | USB & Bluetooth | USB |
| Program | Multiscan S/W & Multiload S/W | |
| Demension | 85(W)*160(H)*40(D)mm | |
| Power | DC 12 V | USB |
| Usb to Bluetooth | GT-UB2 | |